

C++ Basics 1

CS 16: Solving Problems with Computers I
Lecture #3

Ziad Matni
Dept. of Computer Science, UCSB

Announcements

- **Homework #2 due today**
- Homework #3 due Thursday
- **Class is closed to new registration**
- **No more switching lab times**

Lecture Outline

- Variables and Assignments
- Input and Output
- Data Types and Expressions

REVIEW

```
1  #include <iostream>
2  using namespace std;
3  int main()
4  {
5      int number_of_pods, peas_per_pod, total_peas;
6      cout << "Press return after entering a number.\n";
7      cout << "Enter the number of pods:\n";
8      cin >> number_of_pods;
9      cout << "Enter the number of peas in a pod:\n";
10     cin >> peas_per_pod;
11     total_peas = number_of_pods * peas_per_pod;
12     cout << "If you have ";
13     cout << number_of_pods;
14     cout << " pea pods\n";
15     cout << "and ";
16     cout << peas_per_pod;
17     cout << " peas in each pod, then\n";
18     cout << "you have ";
19     cout << total_peas;
20     cout << " peas in all the pods.\n";
21     return 0;
22 }
```

```
Press return after entering a number.
Enter the number of pods:
10
Enter the number of peas in a pod:
9
If you have 10 pea pods
and 9 peas in each pod, then
you have 90 peas in all the pods.
```

1-4: Program start
5: Variable declaration
6-20: Statements
21-22: Program end

`cout << "some string or another" ;`
`cin >> some_variable;`

output stream statement

input stream statement

stream is an entity where a program can either insert or extract characters

cout* and *cin* are **objects** defined in *iostream

Variables

- A **variable** is a *symbolic* reference to data
- The variable's **name** represents *what* information it contains
- They are called “**variables**” because the *data can change* while the **operations** on the variable remain the same
 - The variables “a” and “b” can take on different values, but I may always want to add them together
- If two variables are of the same **type**, you can perform **operations** on them

Variables in C++

- In C++, variables are placeholders for memory locations in the CPU
- We can assign a value to them
- We can change that value stored
- BUT we cannot erase the memory location of that particular variable

Types of C++ Variables: General

- There are 3 properties to a variable: Variables have a **name (identifier)**, a **type**, and a **value** attached to them
- **Integers**
 - Whole numbers
 - Example: 122, 53, -47
- **Floating Point**
 - Numbers with decimal points
 - Example: 122.5, 53.001, -47.201
- **Boolean**
 - Takes on one of two values: “true” or “false”
- **Character**
 - A single alphanumeric
 - Example: “c”, “H”, “%”
 - Note the use of quotation marks
- **String**
 - A string of characters
 - Example: “baby”, “what the !@\$?”
 - Note the use of quotation marks

There are many other types of variables

About Variable Names

- **Good variable name:** indicates what data is stored inside it
- *They should make sense to a non computer programmer*
 - Avoid generic names

- Example:

`name = "Bob Roberts"` is not descriptive enough,

but

`candidate_name = "Bob Roberts"` is better

About Variable Names

- The **name of the variable is not the information!**
 - Example: `class_size = 40` is good, but
`class_size_is_40 = TRUE` is bad
- Variable names must adhere to certain rules.
**In C++,
they MUST start with either a letter or an underscore (_)**
- The rest of the letters can be alphanumeric or underscores.
- They cannot start with a number
- They cannot contain spaces or dots or other symbols

Reserved Keywords

- Used for specific purposes by C++
- Must be used as they are defined in C++
- Cannot be used as identifiers

EXAMPLE:

You cannot call a variable “int” or “else”

For a list of all C++ keywords, see:

<http://en.cppreference.com/w/cpp/keyword>

Declaring Variables

- Variables in C++ must be declared before they are used in a program!

Declaration syntax:

Type_name *Variable_1* , *Variable_2* , ... ;

Examples:

```
double average, m_score, total_score;
int id_num, height, weight, age, shoesize;
int points;
```

NOTE:

One type of variable is declared at a time

Initializing Variables

- When you declare a variable, it's not created with any value in particular
- It is good practice to initialize variables before using them
 - Otherwise they will contain whatever value is in that memory location

EXAMPLE:

```
int num, doz;  
num = 5;  
doz = num + 7;
```

num is initialized to 5

doz is initialized to (num + 7)

- C++ allows alternative ways to initialize variables as they are declared:

```
int num = 5, doz = 12;
```

OR

```
int num(5), doz(12);
```

Assignment Statements

- Are how one changes the value of a variable.

```
total_weight = 12 * one_weight ;
```

Assignment Statements vs. Algebraic Statements

- C++ syntax is NOT the same as in Algebra

EXAMPLE:

number = number + 3

C++ shortcut:

number += 3

- Is an impossible statement in algebra ($0 = 3$?!?!?!?!!!!!)
- In C++, it means:
 - take the *current* value of “number”,
 - add 3 to it,
 - then reassign that *new value* to the variable “number”

Variable Comparisons

- When variables are being *compared* to one another, we use *different symbols*

- a is equal to b

$a == b$

- a is not equal to b

$a != b$

- a is larger than b

$a > b$ *false*

- a is larger than or equal to b

$a >= b$

- a is smaller than b

$a < b$

- a is smaller than or equal to b

$a <= b$

Note:

*The outcome of these comparisons are always either **true** or*

false

Inputs and Outputs

Data Streams

- **Data stream** = a sequence of data
 - Typically in the form of characters or numbers
- **Input stream** = data for the program to use
 - Typically originates at the keyboard, or from a file
- **Output stream** = the program's output
 - Destination is typically the monitor, or to a file

cout and cin

- Output and input stream objects very popularly used in C++
- To make the definitions of **cin** and **cout** available to a program, you have to declare the statement:

```
#include <iostream>
```

- Using *directives* like that usually includes a collection of *defined names*.
- To make the objects **cin** and **cout** available to our program, you should also declare the statement:

```
using namespace std;
```

Examples of Use (cout)

```
cout << number_of_bars << " candy bars\n";
```

- This sends two items to the monitor (display):
 - The value of **number_of_bars**
 - The quoted string of characters " **candy bars\n**" (note the starting space)
 - The '\n' causes a **new line** to be started following the 's' in bars
- Note: a new ***insertion operator*** is used **for each item of output**
- Note: do **not** use single quotes for the strings (more on that later)

Escape Sequences

- Tell the compiler to treat certain characters in a special way
 - \ (back-slash) is the escape character
- Example: To create a newline in the output, we use
 - `\n` – as in, `cout << "\n";`
 - An alternative (new to later versions of C++):
 - `cout << endl;`
- Other escape sequences:
 - `\t` horizontal tab character
 - `\\` backslash character
 - `\"` quote character
 - `\a` audible bell character
- For a more complete list of escape sequences in C++, see:
<http://en.cppreference.com/w/cpp/language/escape>

Formatting Decimal Places

- A common requirement when displaying numbers.

EXAMPLE: Consider the following statements:

```
double price = 78.5;
cout << "The price is $" << price << endl;
```

- Do you want to print it out as:
The price is \$78.5
The price is \$78.50
The price is \$7.850000e01
- Likely, you want the 2nd option
 - You're going to have to DEFINE that ahead of time

Formatting Decimal Places with `cout`

- To specify fixed point notation, use:
`cout.setf(ios::fixed)`
- To specify that the decimal point will always be shown
`cout.setf(ios::showpoint)`
- To specify that *n* decimal places will always be shown
`cout.precision(n)` --- where *n* can be 1, 2, 3, etc...

EXAMPLE:

```
double price = 78.5;
cout.setf(ios::fixed);
cout.setf(ios::showpoint);
cout.precision(2);
cout << "The price is " << price << endl;
```

Inputs via cin

- cin is an input stream bringing data from the keyboard
- The extraction operator (>>) removes data to be used

EXAMPLE:

```
cout << "Enter the number of bars in a package\n";  
cout << " and the weight in ounces of one bar.\n";  
cin >> number_of_bars;  
cin >> one_weight;
```

- This code prompts the user to enter data then
reads 2 data items from **cin**
- The first value read is stored in *number_of_bars*
- The second value read is stored in *one_weight*
- Data entry can be separated by spaces OR by return key when entered

Entering Multiple Data Input Items

- Multiple data items are *best* separated by spaces
- Data is not read until the **Enter** key is pressed
 - This allows user to make corrections

EXAMPLE:

```
cin >> v1 >> v2 >> v3;
```

- Requires **3** space separated values
- So, user might type:
34 45 12 <enter key>

Design Recommendations

- First, prompt the user for input that is desired
 - Use **cout** statements provide instructions

```
cout << "Enter your age: ";  
cin >> age;
```

- Note: absence of a new line before using cin
 - Why?
- Then, echo the input by displaying what was read
 - This gives the user a chance to verify the data entered

```
cout << age << " was entered." << endl;
```

Data Types

Variable Types in C++

1. Integers

int: Basic integer (whole numbers, positive *OR* negative)

- Usually 32 or 64 bits wide
 - So, if it's 32 bits wide (i.e. 4 bytes), **the range is -2^{31} to $+2^{31}$**
Which is: -2,147,483,648 to +2,147,483,647
- You can express even larger integers using:
long int and **long long int**
- You can express only positive integers using:
unsigned int

Variable Types in C++

2. Real (rational) numbers

double: Real numbers, positive *OR* negative

Type **double** can be written in two ways:

- *Simple form* must include a decimal point
 - Examples: 34.1, 23.0034, 1.0, -89.9
- Alternate form: *Floating Point Notation* (Scientific Notation)
 - **3.41e1** means 34.1
 - **3.67e17** means 3670000000000000000.0 (17 digits after “3”)
 - **5.89e-6** means 0.00000589 (6 decimal places before “5”)
- Number **left of e** (for exponent) does not require a decimal point
- The exponent cannot contain a decimal point

Variations on Number Types

- long int
- long double
- short int
- float (a shorter version of “double”)

Variable Types in C++

3. Characters

char: single character

- Can be any single character from the keyboard
- To declare a variable of type char:
char letter;
- Character constants are enclosed in single quotes
char letter = 'a';

Variable Types in C++

4. Strings

string: a collection of characters (a *string* of characters)

- **string** is a **class**, different from the primitive data types discussed so far.
 - We'll discuss classes further in the course
- Using strings requires you to include the “string” module:
#include <string>
- To declare a variable of type string:
string name = “Homer Simpson”;

Note on ‘ vs “

- Single quotes are only used for **char** types
- Double quotes are only used for **string** types
- So, which of these is ok and which isn't?

```
char letter1 = “a”;
```

```
char letter2 = ‘b’;
```

```
string town1 = “Mayberry”;
```

```
string town2 = ‘Xanadu’;
```


Type Compatibilities

- General Rule:
You cannot operate on differently typed variables.
- In general, store values in variables of the *same* type, so that you can operate on them later.
- The following is an example of a type mismatch:

```
int my_var;  
my_var = 2.99;
```
- **If** your compiler allows this, *my_var* will most likely contain the value 2, not 2.99

int \leftrightarrow double

- Variables of type *double* should not be assigned to variables of type *int*
- Variable of type *int*, however, can normally be stored in variables of type *double*

EXAMPLE:

```
double numero;  
numero = 2;
```

- *numero* will contain 2.0

Variable Types in C++

5. Booleans

bool: a binary value of either “true” (1) or “false” (0).

- You can perform LOGICAL operations on this type:
 - `||` Logical OR
 - `&&` Logical AND
 - `|` Bitwise OR
 - `&` Bitwise AND
 - `^` Bitwise XOR
- Also, when doing comparisons, the result is a Boolean type.

EXAMPLE: What will this print out??

```
int a = 44, b = 9;
bool c;
c = (a == b);
cout << c;
```

Arithmetic Operations on Numbers

- Arithmetic operators can be used with any numeric type
 - Usual types of operations: **+** **-** ***** **%** **(for int)**
 - Usual types of operations: **+** **-** ***** **/** **(for double)**
 - Use brackets (...) to ensure required flow of operation
- An *operand* is a number or variable used by the operator
- Result of an operator *depends on the types of operands*
 - If both operands are **int**, the result is **int**
 - If one *or* both operands are **double**, the result is **double**

Division of Type **double**

- Division with at least one operator of type double produces the expected results.

```
double divisor, dividend, quotient;  
divisor = 3;  
dividend = 5;  
quotient = dividend / divisor;
```

quotient will be 1.6666...

- Result is the same if either
dividend or divisor is of type int

Division of Type int

- Don't do this operation (for serious purposes)
- Division between two int types, results in an int answer

```
int divisor, dividend, quotient;  
divisor = 3;  
dividend = 5;  
quotient = dividend / divisor;
```

quotient will be 1, not 1.6666...

- Integer division **does not round the result**, rather the fractional part is discarded!

Modulo Operator (%)

- Shows you the remainder of a division between two **int** types

```
int divisor, dividend, remainder;  
divisor = 3;  
dividend = 5;  
remainder = dividend % divisor;
```

What value will “remainder” will be?

Arithmetic Expressions

- Precedence rules for operators are the same as what you used in your algebra classes
 - EXAMPLE: $x + y * z$ (y is multiplied by z first)
- Use parentheses to force the order of operations (recommended)
 - EXAMPLE: $(x + y) * z$ (x and y are added first)

Operations on Variables

- You *should* only perform operations on **same-type variables**
- Certain operations only work with certain variable types
 - C++ compilers are not always consistent with this...

Examples:

- Say you have 6 variables:
A = 1, B = 2.0, C = "head", D = "and shoulders", E = true, F = false
Integer Double Strings Booleans
- Can you do the following in C++?:
 - A + B ❖ Yes
 - A * B ❖ Yes
 - C + D ❖ Yes
 - A + E ❖ Yes, **BUT NOT RECOMMENDED!!!**
 - E && F ❖ Yes

Operator Shorthands

- Some expressions occur so often that C++ contains shorthand operators for them
- All arithmetic operators can be used this way:
 - `count = count + 2;` ---can be written as--- `count += 2;`
 - `bonus = bonus * 2;` ---can be written as--- `bonus *= 2;`
 - `time = time / factor;` ---can be written as--- `time /= factor;`
 - `remainder = remainder % (cnt1+ cnt2);`
---can be written as--- `remainder %= (cnt1 + cnt2);`

TO DOs

- Readings
 - The rest of Chapter 2, of textbook
- Homework #3
 - Due on Thursday
 - Submit in class
- Lab #2
 - Prepare for it by reading the handout

</LECTURE>